



REVO residential Energy Storage inverters

## American ESS split-phase inverter

battery voltage: 48V



### Product features:

#### Safe & reliable

- Passed UL 1741:2021, IEEE 1547.1, UL1699B, South Africa NRS097-2-1:2017 test certification;

#### Friendly & flexible

- Support multi-machine parallel connection;
- Support multi-machine parallel mode sharing a battery pack;  
Single-machine load capacity 100A;



#### Economical & efficient

- Support parallel SOC equalization control and parallel current sharing control;
- Using split-phase topology and eliminating the transformers, to make the system efficiency higher;
- Support the diesel generator and the grid access at the same time;

# Technical specification:

Technical specification	R5KLNA	R6KLNA	R8KLNA	R10KLNA
<b>Input (PV)</b>				
Max. power(kW)	7.5	9	12	13
Max. DC voltage (V)		500		
MPPT voltage range(V)		120~500		
Max.Input current of single MPPT(A)		12		
MPPT tracker/strings		4/1		
<b>AC output</b>				
Rated output power(kVA)	5	6	8	10
Max. output current(A)	24	28.8	38.3	47.8
Ac output voltage(V)	120/240(split phase), 208(2/3 phase),230 (single phase)			
Frequency (Hz)		50/60		
PF	0.8lagging-0.8leading			
THDi	< 3%			
AC output topology	Split phase, 2/3 phase, single phase			
<b>Battery</b>				
Battery voltage range(V)		40~58		
Max. charging voltage(V)		58		
Max. charge/discharge current(A)	120/120	135/135	190/190	210/210
Battery type	lithium /Lead-acid			
Communication interface	CAN/RS485			
<b>EPS output</b>				
Rated power(kVA)	5	6	8	10
Rated output voltage(V)	120/240 (split phase), 208 (2/3 phase),230 (single phase)			
Rated output current(A)	24	28.8	38.3	47.8
Rated frequency(Hz)		50/60		
Automatic switching time(ms)		<20		
THDu		< 2%		
Overload capacity	125%,60S/150%,1S			
<b>General data</b>				
Max. efficiency		≥98.2%		
North american efficiency		≥97.2%		
Ingress protection		IP65/NEMA 3R		
Noise emission(dB)	<25	<29	<29	<29
Operation temperature		-25°C ~ 60°C		
Cooling		Natural		
Relative humidity		0 ~95% (non-condensing)		
Altitude		2,000m(>2,000 Derating)		
Dimensions W *D *H (mm)		430*220*710		
Weight(kg)		41		
Isolation transformer		No		
Self-consumption(W)		<3		
<b>Display and communication</b>				
Display	LCD, touch screen			
Interface:RS485/Wifi/4G/ CAN/DRM		Yes		
Safety standard	UL1741SA all options, UL1699B, CSA 22.2			
EMC	FCC Part 15, Class B			
On-grid	IEEE 1547, IEEE 2030.5, Hawaii Rule 14H, Rule 21 Phase I,II,III,NRS			

